

Push-in plug IV with float housing

Technical data



A4N000 is universally applicable.

Float freely selectable
(see floats table).



for: T 54 ... 58mm / 2.13 ... 2.28"
T1 = 54mm / 2.13"
T2 = 36mm / 1.42"

applicable for cell depth
(T) 54 ... 58mm / 2.13 ... 2.28"

(T = top of the cell to top of separator)

Filling level (T2) 36mm / 1.42"

(T2 = max. filling level,
top of cell to top of electrolyte level)



for: T 58 ... 62mm / 2.28 ... 2.44"
T1 = 58mm / 2.28"
T2 = 38mm / 1.50"

applicable for cell depth
(T) 58 ... 62mm / 2.28 ... 2.44"

(T = top of the cell to top of separator)

Filling level (T2) 38mm / 1.50"

(T2 = max. filling level,
top of cell to top of electrolyte level)



for: T 62 ... 66mm / 2.44 ... 2.60"
T1 = 62mm / 2.44"
T2 = 40mm / 1.57"

applicable for cell depth
(T) 62 ... 66mm / 2.44 ... 2.60"

(T = top of the cell to top of separator)

Filling level (T2) 40mm / 1.57"

(T2 = max. filling level,
top of cell to top of electrolyte level)

