



hose 6mm

hose clamp NW6

end piece

hose 10mm

hose clamp NW10

filter cartridge

male connection

dust cap

bfs-plug III

float

gasket 3mm

T-piece 6/10/6



bayonet plug III  
B51000

1	12	bfs-plug III	B51000
1a	12	float 07.....	07.....
1b	12	gasket	09DI30
2	1	T-piece 6/10/6 mm	08T616
3	4m	hose 6mm	08SCH6
4	2m	hose 10mm	08SCH1
5	2	end piece	08END6
6	1	dust cap	09STAC
7	24	hose clamp 6mm	08KLE6b
8	1	hose clamp 10mm	08KLE1
9	1	filter cartridge	09FIL1b
10	1	connection male	09KUV1b
Pos.	Quant.	Description	Part No.

Maßstab/SCALE:

2000 Datum Name

Bearb. 20.09. Scher

Gepr.

Norm

Werkstoff/MATERIAL:

SAMPLE FOR THE PIPING OF

A 24 VOLT BATTERY

Zeichnungs-Nr. / DWG NO.

**bfs**

Ing. Klaus Oschmann

Mitterweg 9 - 11

85230 Bergkirchen

nicht tolerierte Freißeite nach DIN 16901

UNLESS OTHERWISE SPECIFIED TOLERANCES

POK DIN 3690

Zust. Änderung Datum Name

Drawings made available by bfs as to the layout or water pipes for battery filling systems are only examples, which require adaptation for each specific battery grouping. The person responsible for the installation of a battery filling system including the water pipes is also responsible to ensure that all instructions given by the producer of the batteries as well as all relevant instructions by the European Union are followed carefully.

(see for instance EU instruction EN 50272 Para 10.2)